

RHOCT-**R**

Retail truck series

YUNLIHONG

Shiyan Yunlihong Industrial & Trade Co., Ltd.

十堰市郢利宏工贸有限公司

|               |                                    |
|---------------|------------------------------------|
| CHASSIS MODEL | R42GV8.2E2D3.9 Retail truck series |
| TRUCK NAME    | 6 tons Cargo Truck                 |
| DRIVE TYPE    | 4×2                                |

# RHOCT- R Model Range

R42GV8.2E2D3.9 Retail truck series - GCW 9.5 tons

Yunlihong Trucks. Driving Progress



| Chassis Dimensions [mm] |                                      |      | Plated Weights [kg]      |  | Plated | Design |
|-------------------------|--------------------------------------|------|--------------------------|--|--------|--------|
| WB                      | Wheelbase                            | 3800 | Gross Vehicle Weight     |  | 8200   | 9840   |
| C                       | Cargo box Length space               | 5150 | Gross Combination Weight |  | -      | -      |
| A                       | Overall Chassis Length               | 6995 | Front Axle               |  | 2700   | 3240   |
| D                       | Center of rear axle to front of body | 4550 | Rear Axle                |  | 5500   | 6600   |
| T                       | Theoretical Wheelbase                | -    | Support Axle             |  |        |        |
| N                       | Rear Overhang                        | 2210 |                          |  |        |        |

- Due to the large gap in laws and regulations in various countries, 'plated GCW' is not displayed. Please select a vehicle according to local regulations and 'Design GCW'.

# RHOCT- R Model Range

Yunlihong Trucks. Driving Progress



R42GV8.2E2D3.9 Retail truck series - GCW 9.5 tons



## TRUCK USE

|          |                                                |
|----------|------------------------------------------------|
| OC-ONWC  | Operating class on road, wet concrete pavement |
| PRE-TIPP | Tipper vehicle preparation                     |

## CORE COMPONENTS

|          |                                                                                                                                                                                                   |
|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CHH-S    | Chassis height S High - Standard height. For a specific loading height always check the unique BEP chassis drawing                                                                                |
| FS-L90   | 90mm 'S' parabolic front springs                                                                                                                                                                  |
| RDS-L90  | 90mm 'S' parabolic rear springs                                                                                                                                                                   |
| DO-DS    | Standard cab - with steel safety cage design<br>Day cab - 3 seats<br>High Power Audio system: RDS radio - also playing MP3/WMA files, with USB/Line inputs. FM/AM antenna, speakers in dashboard, |
| E2D3.9   | Emission level - Euro 2 engine 3.9L displacement                                                                                                                                                  |
| B125-20  | Cummins B125-20 3.9 litre engine developing 125hp at 2500rpm. Peak torque 410Nm at 1500rpm.                                                                                                       |
| 6DS60T-D | Fast (Eaton Technology) 6-speed direct manual mechanical gearbox suitable for engines with maximum torque not exceeding 600Nm, maximum horsepower not exceeding 140hp,                            |
| SF-2700  | Front steer axles design capacity 3.24 tonnes - 3.24 tonne Front steer axles.                                                                                                                     |
| DRS-5500 | Rear drive axles design capacity 6.6 tonnes - 6.6 tonne rear drive axles. Maximum output torque 15000N.m                                                                                          |
| None     | No support axle                                                                                                                                                                                   |

# RHOCT- R Model Range

Yunlihong Trucks. Driving Progress



R42GV8.2E2D3.9 Retail truck series - GCW 9.5 tons



## CHASSIS

|            |                                                                                                                   |
|------------|-------------------------------------------------------------------------------------------------------------------|
| FS-PAR8    | 8 leaf springs suspension, 90mm wide springs                                                                      |
| HPSP-FIX   | Hydraulic power steering pump with fixed displacement                                                             |
| RDS 10+7   | 10+7 leaf springs suspension, 90mm wide springs                                                                   |
| FROB       | Front brake -Drum brake is standard configuration, optional disc brake                                            |
| REAB       | Rear brake -Drum brake is standard configuration, optional disc brake                                             |
| BAA        | Brake adjusting arm, optional auto brake adjusting arm                                                            |
| APB        | Auxiliary parking brake - Additional spring brakes                                                                |
| FRAME192   | Frame rail section external height 192 mm                                                                         |
| FW65       | Frame width - 65mm                                                                                                |
| FST6       | Frame thickness - flange 6 mm                                                                                     |
| BBOX       | Battery box located on whichever side based on final chassis layout                                               |
| BAT        | 2 x 90 Ah capacity batteries is standard configuration                                                            |
| MSWI-C     | Main switch - Chassis mounted toggle switch by battery box                                                        |
| FT125S     | Steel fuel tank, 125 litres volume. Min volume 125l, Max volume 400l                                              |
| ADTP-NO    | No AdBlue tank                                                                                                    |
| FCAP       | Locking fuel filler cap is option.                                                                                |
| FF         | You can install both fuel filling anti-theft and anti-spillage devices, or you can choose one of them. (optional) |
| SEO-HR     | Tow member - High mounted in centre of frame                                                                      |
| TOWF-NO1   | Front towing device - One pin in bumper                                                                           |
| TOWR-ONE L | Light trailer coupling - Pintle type hitch attached to rear cross member for an unbraked trailer. (optional)      |
| SEO-HR     | Horizontal silencer, rear exhaust outlet. Exhaust outlet located on whichever side based on final chassis layout  |
| LPB-F      | Front lower position bumper                                                                                       |
| DAN        | Some modified for transportation of dangerous goods on the road. (optional)                                       |




# RHOCT- R Model Range

Yunlihong Trucks. Driving Progress



R42GV8.2E2D3.9 Retail truck series - GCW 9.5 tons



## CAB EXTERIOR & INTERIOR

|                  |                                                                                                                                                         |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>WLIFT-EDP</b> | Electrical window lift, automatic up/down driver side & passenger side                                                                                  |
| <b>ISV-BS</b>    | Side interior sun visor on both sides                                                                                                                   |
| <b>BUPALARM</b>  | Reverse alarm                                                                                                                                           |
| <b>UPHTRI10</b>  | Seats: Black embossed textile insert with light grey sides, black side bolster insert.<br>Interior trim: light grey bunk, curtains & textile side walls |
| <b>DST</b>       | Driver seat, comfort, mechanical cushioning seats, belt in cab                                                                                          |
| <b>PST</b>       | Passenger seat - Fixed non suspended fold up with seatbelt mounted in cab                                                                               |
| <b>BEDW</b>      | Bed width - x -mm                                                                                                                                       |
| <b>FCABS-M</b>   | Front cab suspension - Mechanical spring                                                                                                                |
| <b>RCABS-M</b>   | Rear cab suspension - Mechanical spring                                                                                                                 |
| <b>CTILTP</b>    | Manually operated hydraulic cab tilt                                                                                                                    |
| <b>AUXFS</b>     | Lower swinging cab step                                                                                                                                 |
| <b>BUMP-MD</b>   | Heavy duty front bumper                                                                                                                                 |
| <b>HL-ADJ</b>    | Headlight adjustment - Switch in cab                                                                                                                    |

## WHEELS & TYRES

|                 |                                                                                                                                                                                                                                                                                               |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>RIM</b>      | Steel rims on all axles is standard configuration, optional alcoa Dura-Bright aluminium rims - standard holes for long stud fixing                                                                                                                                                            |
| <b>SPWT</b>     | Spare wheel tyre & front wheel & rear wheel tyre with same pattern                                                                                                                                                                                                                            |
| <b>SWCP</b>     | Side mounted spare wheel carrier                                                                                                                                                                                                                                                              |
| <b>TIRE-PER</b> | New trendy pattern design.<br>Anti-eccentric abrasion, good self-cleaning performance.<br>Sufficient driving performance and stable handling performance<br>Suitable for all wheel positions of long-distance, high-speed passenger and freight vehicles, driving at high speed on good roads |

# RHOCT- **R** Model Range

Yunlihong Trucks. Driving Progress



R42GV8.2E2D3.9 Retail truck series - GCW 9.5 tons



## OPTIONAL CONFIGURATION

|          |                           |
|----------|---------------------------|
| AF-TS    | Two stage air filter      |
| PRIM-MAN | Manual priming pump       |
| FLEH     | Fuel line electric heater |
| PTO      | Full power PTO            |
| STGW-ADJ | Adjustable steering wheel |
| AD-ROOF  | Roof air deflector        |
| HLP-ST   | Headlamp protection       |

## OPTIONAL TOOL

|          |                                                                    |
|----------|--------------------------------------------------------------------|
| TOOL     | Toolkit                                                            |
| JACK-12T | 12 tonne bottle jack / 15 tonne bottle jack / 20 tonne bottle jack |
| INFLAHOS | Tyre inflation hose                                                |
| GAUGE-TP | Tyre pressure gauge                                                |
| WHC-FIX2 | Two fixed wheel chocks                                             |
| SC       | Snow chains                                                        |
| SCH      | Snow chain hooks                                                   |
| TOW      | One heavy duty front towing device                                 |
| FIREXT3S | 3kg fire extinguisher mounted on seat base                         |
| WARNVEST | High visibility warning vest - no sleeves                          |
| AIDKIT   | First aid kit                                                      |
| WARNLAMP | Portable warning lamp                                              |
| LAMP-IN  | Inspection lamp                                                    |
| BULBKIT  | Bulb and fuse kit                                                  |
| WRITEPAD | Writing pad                                                        |


# RHOCT- R Model Range

R42GV8.2E2D3.9 Retail truck series - GCW 9.5 tons

Yunlihong Trucks. Driving Progress



## PERFORMANCE



When the GCW of the vehicle is 9.5 tons,  
The maximum gradeability of the vehicle is 26.1%, and the angle is about 14.63°.  
When the gradeability of the vehicle is 15%, the angle is about 8.53°, and the maximum speed at this time is 32km/h.  
The top speed of the vehicle is 98km/h, and the economic speed is 64km/h.

### Test Conditions

|                              |                   |                                        |      |
|------------------------------|-------------------|----------------------------------------|------|
| Road surface                 | Concrete pavement | Wind resistance area (m <sup>2</sup> ) | 3.24 |
| Coefficient of road adhesion | 0.85              | Altitude (m)                           | 0    |

### Test vehicle configuration

|              |             |              |          |
|--------------|-------------|--------------|----------|
| Engine       | B125-20     | Front axle   | SF-2700  |
| Transmission | 6DS60T-D    | Rear axle    | DRS-5500 |
| Tire         | 215/75R17.5 | Support axle | None     |

# RHOCT- R Model Range

Yunlihong Trucks. Driving Progress



R42GV8.2E2D3.9 Retail truck series - GCW 9.5 tons

## ASSEMBLY PERFORMANCE

### Engine

B125-20

|        |      |      |      |      |      |      |      |      |     |  |  |  |
|--------|------|------|------|------|------|------|------|------|-----|--|--|--|
| Speed  | 2500 | 2300 | 2100 | 1900 | 1700 | 1500 | 1300 | 1100 | 900 |  |  |  |
| Torque | 287  | 324  | 349  | 369  | 390  | 410  | 390  | 369  | 349 |  |  |  |

### Transmission

6DS60T-D

|       |      |     |      |      |     |      |  |  |  |  |  |  |
|-------|------|-----|------|------|-----|------|--|--|--|--|--|--|
| Gear  | 1st  | 2nd | 3rd  | 4th  | 5th | 6th  |  |  |  |  |  |  |
| Ratio | 0.78 | 1   | 1.52 | 2.41 | 4   | 6.64 |  |  |  |  |  |  |

### Tire

215/75R17.5

| Model       | Speed<br>(km/h) | Width<br>(mm) | Diameter<br>(mm) | 层级 | Capacity (kg) |        | Pressure (kPa) |        |
|-------------|-----------------|---------------|------------------|----|---------------|--------|----------------|--------|
|             |                 |               |                  |    | Single        | Double | Single         | Double |
| 215/75R17.5 | 120             | 211           | 767              | 16 | 2180          | 2060   | 860            | 860    |

### Dimension

|                |      |  |  |  |  |  |  |
|----------------|------|--|--|--|--|--|--|
| Wheelbase      | 3800 |  |  |  |  |  |  |
| Cargo Length   | 5150 |  |  |  |  |  |  |
| Cargo Height   | 550  |  |  |  |  |  |  |
| Overall Length | 6995 |  |  |  |  |  |  |

YUNLIHONG

Yunlihong Truck Corporation  
hbylh.com

Ref: R42GV8.2E2D3.9



















